



天元化工
TanYun Chemicals

ADD: West Xihu Street, Coastal Industrial Base, Yingkou, 115004, Liaoning, China

P.O.CODE:115004

TEL:0417-2827700

Email: chinasupplierfrank@qq.com

FAX:0417-2821100

Http:www.tanyun.com.cn



Material Safety Data Sheet

Caution: Contains diphenyl methane 4.4 diisocyanate. Keep away from heat, sparks, flames and static electricity. Vapors heavier than air may cause flash fire or ignite explosively. Do not puncture, expose to heat or store at temperatures above +50c.

- 1) The foam is adhesive on the skin and clothes.
- 2) Please do not let the foam touch the skin and clothing when using.

- 3) Its one-component polyurethane foam tank has 5-6kg / cm² (25 °C) pressure so storage and transportation process temperature should not exceed 50 °C, to prevent the occurrence tank blasting.
- 4) Empty cans after use.
- 5) Construction site should have ventilation.
- 6) Workers in construction should wear work gloves,
- 7) Coveralls and goggles.
- 8) In case the foam contacts with eyes please flush with water for 15 minutes and seek medical assistance.
- 9) If ingested seek medical assistance
- 10) If foam is wet remove immediately with acetone or polyurethane foam cleaner. After removal wash with soap water. If the foam has dried, it is very difficult to remove. Do not try to remove with solvents. Cured foam wears off and is not harmful to health.